



**Haco Atlantic
Pressbrakes
ATP**



**Haco Atlantic
Shears
ATS**



**Haco Atlantic
CNC Punching
Machines ATT**



Impressive Performances

Revolutionary Prices

Pressbrakes ATP



Model 3200 mm x 1000 kN

Technical Specifications Haco Atlantic ATP Pressbrakes

Model	Working length	Capacity	Distance between Houings	Gap	Daylight Opening	Stroke	Table Height	Table Width	
	mm	kN	mm	mm	mm	mm	mm	mm	
15063	1500	630	1100	370	350	200	880	150	
25063	2500	630	2060	370	350	200	880	150	
32100	3200	1000	2700	400	400	200	880	200	
42100	4200	1000	3700	400	400	200	880	200	
32135	3200	1350	2700	400	400	200	880	200	
42135	4200	1350	3700	400	400	200	880	200	
32160	3200	1600	2700	400	400	200	880	200	
42160	4200	1600	3700	400	400	200	880	200	
32250	3200	2500	2700	400	400	200	880	200	
42250	4200	2500	3700	400	400	200	880	200	
30300	3000	3000	2500	400	400	200	880	250	
40300	4000	3000	3150	400	400	200	880	250	
50300	5000	3000	4050	400	400	200	880	250	
40400	4000	4000	3150	400	400	320	880	250	
50400	5000	4000	4050	400	400	320	880	250	
60400	6000	4000	5050	400	400	320	880	250	
40500	4000	5000	3050	400	610	320	990	300	
50500	5000	5000	4050	400	610	320	990	300	
60500	6000	5000	5050	400	610	320	990	300	
60600	6000	6000	5050	400	650	320	990	300	

(*) Only with Optional Safety Guard



Standard Execution

- Robosoft Electro-hydraulic ram-table parallelism and depth stop setting
- Pendant control panel with graphical control EasyBEND-2D
- Backgauge on ballscrews, stroke 500mm, programmable in 0.1mm
- Programmable working pressure, ram stroke, ram opening and speed change-over point
- Programmable automatic beam return
- Automatic hydraulic table crowning
- Quick manual System Top Tooling clamping
- Table for System Tooling
- 2 Sheet Supports
- Foot pedal command
- CE Safety Specifications

Optional

- Backgauge X-R or X-R-Z1/Z2
- DSP Optical Safety Guard

Fast * Approach Speed	Max. Working Speed	Return Speed	Motor	length +/-	Width +/-	Height +/-	Weight +/-	Backgauge stroke
mm/s	mm/s	mm/s	kW	mm	mm	mm	kg	mm
100	10	80	5.5	1825	1650	2600	4600	500
100	10	80	5.5	2825	1650	2430	5600	500
100	10	80	7.5	3500	1650	2540	8000	500
100	10	80	7.5	4500	1650	2540	9500	500
100	10	80	11	3500	1650	2540	8500	500
100	10	80	11	4500	1650	2540	10000	500
100	10	100	11	3500	1650	2580	10000	500
100	10	100	11	4500	1650	2580	12000	500
100	10	100	15	3500	1730	2580	15000	500
100	10	100	15	4500	1730	2580	17000	500
80	8	85	18.5	3300	1950	2670	20000	500
80	8	85	18.5	4300	1950	2670	22000	500
80	8	85	18.5	5300	1950	2620	26000	500
80	8	80	30	4300	2100	3100	27000	500
80	8	80	30	5300	2100	3100	32000	500
80	8	80	30	6400	2100	3170	38000	500
75	8	75	37	4500	2700	5000	40000	700
75	8	75	37	5500	2700	5000	45000	700
75	8	75	37	6500	2700	5000	55000	700
80	8	80	40	6500	2700	5200	65000	700